



--- 2020-Cigarette



DESCRIPTION

Sarah Coleman is a New York City based visual artist who is inspired by both high luxury and everyday items. Nostalgia and play drives much of her subversive approach to making art. Leveraging designer materials, playing off logos, and honoring legacy brand archives, Coleman gives repurposed objects a chance at another life. To describe her color selection, Coleman says, "They speak for themselves – they're humorous."

CONFIGURED BY SARAH COLEMAN

New York, USA | 06:39:03 PM | 04.12.2022

DIMENSIONS

Length: 48"
Diameter: 8"


QTY OF LIGHTS

8" Diameter x 6

FELT



Graphit Gletscher Rost



Senf Wollweiß

PLATE



Black



Champagne

CANOPY



White

CABLE



White

CERTIFICATION

ETL certified (UL equivalency)
Dry indoor use only

POWER

Power supply:

- 12 VDC output Class 2 constant voltage integral power supply
- Integral power supply in Standard Canopy can support up to 10 light discs
- Integral power supply in Multi-fixture Canopy can support up to 25 light discs
- Remote drive options upon request
- Casambi, DALI, Luton Compatible

Controls:

120/227 V input, TRIAC, ELV, 0-10 dimming

Input voltage:

120 VAC (277 VAC upon request)

Lamping:

7.4 W per 8" light disc, CRI 90,
L80 50,000 hours

Lumens delivered:

585 lm per 8" light disc

LIGHT DISC TEMP

2200 K/2700 K/3000 K/3500 K

ACOUSTICS

Felt NRC: 0.2
Sound absorption (sabins): 1.78

MAINTENANCE

Lint roll occasionally to remove general air-borne debris. Should soiling occur, spot clean with mild soap and lukewarm water. Avoid aggressive rubbing as this can continue the felting process and change the surface appearance of the felt.

PRODUCTION LEAD TIME

6-10 weeks

ASSEMBLED IN TORONTO, CANADA

Please note that our remnants are sourced from different lots, and color variations may occur



--- 2021-Shotgun Shell



DESCRIPTION

Sarah Coleman is a New York City based visual artist who is inspired by both high luxury and everyday items. Nostalgia and play drives much of her subversive approach to making art. Leveraging designer materials, playing off logos, and honoring legacy brand archives, Coleman gives repurposed objects a chance at another life. To describe her color selection, Coleman says, "They speak for themselves – they're humorous."

CONFIGURED BY SARAH COLEMAN

New York, USA | 06:39:03 PM | 04.12.2022


DIMENSIONS

Length: 32"
Diameter: 5"

QTY OF LIGHTS

5" Diameter x 3

FELT



Rost



Senf

PLATE



Champagne

CANOPY



White

CABLE



Gold

CERTIFICATION

ETL certified (UL equivalency)
Dry indoor use only

POWER

Power supply:

- 12 VDC output Class 2 constant voltage integral power supply
- Integral power supply in Standard Canopy can support up to 10 light discs
- Integral power supply in Multi-fixture Canopy can support up to 25 light discs
- Remote drive options upon request
- Casambi, DALI, Luton Compatible

Controls:

120/227 V input, TRIAC, ELV, 0-10 dimming

Input voltage:

120 VAC (277 VAC upon request)

Lamping:

3.7 W per 5" light disc

Lumens delivered:

350 lm per 5" light disc

LIGHT DISC TEMP

2200 K/2700 K/3000 K/3500 K

ACOUSTICS

Felt NRC: 0.2

Sound absorption (sabins): 0.77

MAINTENANCE

Lint roll occasionally to remove general air-borne debris. Should soiling occur, spot clean with mild soap and lukewarm water. Avoid aggressive rubbing as this can continue the felting process and change the surface appearance of the felt.

PRODUCTION LEAD TIME

6-10 weeks

ASSEMBLED IN TORONTO, CANADA

Please note that our remnants are sourced from different lots, and color variations may occur



--- 2022-Pregnancy Test



DESCRIPTION

Sarah Coleman is a New York City based visual artist who is inspired by both high luxury and everyday items. Nostalgia and play drives much of her subversive approach to making art. Leveraging designer materials, playing off logos, and honoring legacy brand archives, Coleman gives repurposed objects a chance at another life. To describe her color selection, Coleman says, "They speak for themselves – they're humorous."

CONFIGURED BY SARAH COLEMAN

New York, USA | 12:47:43 PM | 04.13.2022


DIMENSIONS

Length: 48"
Diameter: 5"


QTY OF LIGHTS

5" Diameter x 6

FELT




PLATE



CANOPY



CABLE



CERTIFICATION

ETL certified (UL equivalency)
Dry indoor use only

POWER

Power supply:

- 12 VDC output Class 2 constant voltage integral power supply
- Integral power supply in Standard Canopy can support up to 10 light discs
- Integral power supply in Multi-fixture Canopy can support up to 25 light discs
- Remote drive options upon request
- Casambi, DALI, Luton Compatible

Controls:

120/227 V input, TRIAC, ELV, 0-10 dimming

Input voltage:

120 VAC (277 VAC upon request)

Lamping:

3.7 W per 5" light disc

Lumens delivered:

350 lm per 5" light disc

LIGHT DISC TEMP

2200 K/2700 K/3000 K/3500 K

ACOUSTICS

Felt NRC: 0.2
Sound absorption (sabins): 1.16

MAINTENANCE

Lint roll occasionally to remove general air-borne debris. Should soiling occur, spot clean with mild soap and lukewarm water. Avoid aggressive rubbing as this can continue the felting process and change the surface appearance of the felt.

PRODUCTION LEAD TIME

6-10 weeks

ASSEMBLED IN TORONTO, CANADA

Please note that our remnants are sourced from different lots, and color variations may occur



Hombre-Short



DESCRIPTION

No stranger to the lighting world, Keeler worked for internationally acclaimed interior design studios and innovative LED luminaire producers before opening his own studio. Keeler, who helped Stackabl develop its first pendant collection, chose a neutral color selection and ombre effect to show off the light’s verticality and versatility. “Arranging them in a cluster can really define height and showcase the architecture of a space.”

CONFIGURED BY ANTHONY FRANK KEELER

Toronto, Canada | 04:42:23 PM | 04.11.2022


DIMENSIONS

Length: 18”
Diameter: 8”

QTY OF LIGHTS


8” Diameter x 4

FELT



Asche Graphit Weiß

PLATE




Clear

CANOPY



White

CABLE



White

CERTIFICATION

ETL certified (UL equivalency)
Dry indoor use only

POWER

Power supply:

- 12 VDC output Class 2 constant voltage integral power supply
- Integral power supply in Standard Canopy can support up to 10 light discs
- Integral power supply in Multi-fixture Canopy can support up to 25 light discs
- Remote drive options upon request
- Casambi, DALI, Luton Compatible

Controls:

120/227 V input, TRIAC, ELV, 0-10 dimming

Input voltage:

120 VAC (277 VAC upon request)

Lamping:

7.4 W per 8” light disc, CRI 90, L80 50,000 hours

Lumens delivered:

585 lm per 8” light disc

LIGHT DISC TEMP

2200 K/2700 K/3000 K/3500 K

ACOUSTICS

Felt NRC: 0.2
Sound Absorption (sabins): 0.67

MAINTENANCE

Lint roll occasionally to remove general air-borne debris. Should soiling occur, spot clean with mild soap and lukewarm water. Avoid aggressive rubbing as this can continue the felting process and change the surface appearance of the felt.

PRODUCTION LEAD TIME

6-10 weeks

ASSEMBLED IN TORONTO, CANADA

Please note that our remnants are sourced from different lots, and color variations may occur



--- Hombre-Long



DESCRIPTION

No stranger to the lighting world, Keeler worked for internationally acclaimed interior design studios and innovative LED luminaire producers before opening his own studio. Keeler, who helped Stackabl develop its first pendant collection, chose a neutral color selection and ombre effect to show off the light’s verticality and versatility. “Arranging them in a cluster can really define height and showcase the architecture of a space.”

CONFIGURED BY ANTHONY FRANK KEELER

Toronto, Canada | 01:20:21 PM | 04.11.2022


DIMENSIONS

Length: 48”
Diameter: 8”

QTY OF LIGHTS

8” Diameter x 6

FELT




Asche

Graphit

Weiß

PLATE




Clear

CANOPY



White

CABLE



White

CERTIFICATION

ETL certified (UL equivalency)
Dry indoor use only

POWER

Power supply:

- 12 VDC output Class 2 constant voltage integral power supply
- Integral power supply in Standard Canopy can support up to 10 light discs
- Integral power supply in Multi-fixture Canopy can support up to 25 light discs
- Remote drive options upon request
- Casambi, DALI, Lutron Compatible

Controls:

120/227 V input, TRIAC, ELV, 0-10 dimming

Input voltage:

120 VAC (277 VAC upon request)

Lamping:

7.4 W per 8” light disc, CRI 90,
L80 50,000 hours

Lumens delivered:

585 lm per 8” light disc

LIGHT DISC TEMP

2200 K/2700 K/3000 K/3500 K

ACOUSTICS

Felt NRC: 0.2

Sound Absorption (sabins): 1.78

MAINTENANCE

Lint roll occasionally to remove general air-borne debris. Should soiling occur, spot clean with mild soap and lukewarm water. Avoid aggressive rubbing as this can continue the felting process and change the surface appearance of the felt.

PRODUCTION LEAD TIME

6-10 weeks

ASSEMBLED IN TORONTO, CANADA

Please note that our remnants are sourced from different lots, and color variations may occur



Hugo



DESCRIPTION

Wisse Trooster is a passionately curious designer from The Netherlands and works with a variety of materials and in multiple disciplines. “The lights match as a family,” Trooster says, “in fact, the names are from Donald Duck’s triplet nephews. Fun, they are interesting on their own but come to life when placed together. The close-to-black and white pattern seamlessly integrates the light discs and by keeping the lamp in one color, the lights became well-balanced.”

CONFIGURED BY WISSE TROOSER

Amsterdam, NL | 03:20:12 PM | 04.10.2022


DIMENSIONS

Length: 18”
Diameter: 8”


QTY OF LIGHTS

5” Diameter x 4
8” Diameter x 2

FELT



PLATE



CANOPY



CABLE



CERTIFICATION

ETL certified (UL equivalency)
Dry indoor use only

POWER

Power supply:

- 12 VDC output Class 2 constant voltage integral power supply
- Integral power supply in Standard Canopy can support up to 10 light discs
- Integral power supply in Multi-fixture Canopy can support up to 25 light discs
- Remote drive options upon request
- Casambi, DALI, Luton Compatible

Controls:

120/227 V input, TRIAC, ELV, 0-10 dimming

Input voltage:

120 VAC (277 VAC upon request)

Lamping:

3.7 W per 5” light disc / 7.4 W per 8” light disc,
CRI 90, L80 50,000 hours

Lumens delivered:

350 lm per 5” light disc / 585 lm per 8” light disc

LIGHT DISC TEMP

2200 K / 2700 K / 3000 K / 3500 K

ACOUSTICS

Felt NRC: 0.2
Sound absorption (sabins): 0.51

MAINTENANCE

Lint roll occasionally to remove general air-borne debris. Should soiling occur, spot clean with mild soap and lukewarm water. Avoid aggressive rubbing as this can continue the felting process and change the surface appearance of the felt.

PRODUCTION LEAD TIME

6-10 weeks

ASSEMBLED IN TORONTO, CANADA

Please note that our remnants are sourced from different lots, and color variations may occur



LUIS



DESCRIPTION

Wisse Trooster is a passionately curious designer from The Netherlands and works with a variety of materials and in multiple disciplines. “The lights match as a family,” Trooster says, “in fact, the names are from Donald Duck’s triplet nephews. Fun, they are interesting on their own but come to life when placed together. The close-to-black and white pattern seamlessly integrates the light discs and by keeping the lamp in one color, the lights became well-balanced.”

CONFIGURED BY WISSE TROOSER

Amsterdam, NL | 03:19:52 PM | 04.10.2022

DIMENSIONS

Length: 22”
Diameter: 8”

QTY OF LIGHTS

5” Diameter x 3
8” Diameter x 4

FELT



Ozean




Senf



Weiß

PLATE




Clear

CANOPY



White

CABLE



White

CERTIFICATION

ETL certified (UL equivalency)
Dry indoor use only

POWER

Power supply:

- 12 VDC output Class 2 constant voltage integral power supply
- Integral power supply in Standard Canopy can support up to 10 light discs
- Integral power supply in Multi-fixture Canopy can support up to 25 light discs
- Remote drive options upon request
- Casambi, DALI, Luton Compatible

Controls:

120/227 V input, TRIAC, ELV, 0-10 dimming

Input voltage:

120 VAC (277 VAC upon request)

Lamping:

3.7 W per 5” light disc / 7.4 W per 8” light disc,
CRI 90, L80 50,000 hours

Lumens delivered:

350 lm per 5” light disc / 585 lm per 8” light disc

LIGHT DISC TEMP

2200 K / 2700 K / 3000 K / 3500 K

ACOUSTICS

Felt NRC: 0.2

Sound absorption (sabins): 0.72

MAINTENANCE


Lint roll occasionally to remove general air-borne debris. Should soiling occur, spot clean with mild soap and lukewarm water. Avoid aggressive rubbing as this can continue the felting process and change the surface appearance of the felt.

PRODUCTION LEAD TIME

6-10 weeks

ASSEMBLED IN TORONTO, CANADA

Please note that our remnants are sourced from different lots, and color variations may occur



Paco



DESCRIPTION

Wisse Trooster is a passionately curious designer from The Netherlands and works with a variety of materials and in multiple disciplines. “The lights match as a family,” Trooster says, “in fact, the names are from Donald Duck’s triplet nephews. Fun, they are interesting on their own but come to life when placed together. The close-to-black and white pattern seamlessly integrates the light discs and by keeping the lamp in one color, the lights became well-balanced.”

CONFIGURED BY WISSE TROOSER

Amsterdam, NL | 03:19:35 PM | 04.10.2022

DIMENSIONS

Length: 13”
Diameter: 8”

QTY OF LIGHTS


5” Diameter x 2
8” Diameter x 2

FELT



Petrol Ozean Weiß

PLATE



Clear

CANOPY



White

CABLE



White

CERTIFICATION

ETL certified (UL equivalency)
Dry indoor use only

POWER

Power supply:

- 12 VDC output Class 2 constant voltage integral power supply
- Integral power supply in Standard Canopy can support up to 10 light discs
- Integral power supply in Multi-fixture Canopy can support up to 25 light discs
- Remote drive options upon request
- Casambi, DALI, Luton Compatible

Controls:

120/227 V input, TRIAC, ELV, 0-10 dimming

Input voltage:

120 VAC (277 VAC upon request)

Lamping:

3.7 W per 5” light disc / 7.4 W per 8” light disc,
CRI 90, L80 50,000 hours

Lumens delivered:

350 lm per 5” light disc / 585 lm per 8” light disc

LIGHT DISC TEMP

2200 K / 2700 K / 3000 K / 3500 K

ACOUSTICS

Felt NRC: 0.2
Sound absorption (sabins): 0.4

MAINTENANCE

Lint roll occasionally to remove general air-borne debris. Should soiling occur, spot clean with mild soap and lukewarm water. Avoid aggressive rubbing as this can continue the felting process and change the surface appearance of the felt.

PRODUCTION LEAD TIME

6-10 weeks

ASSEMBLED IN TORONTO, CANADA

Please note that our remnants are sourced from different lots, and color variations may occur